

Defy Dishmaid 8 Manual



File Name: Defy Dishmaid 8 Manual.pdf

Size: 3336 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 27 May 2019, 23:29 PM

Rating: 4.6/5 from 657 votes.

Status: AVAILABLE

Last checked: 12 Minutes ago!

In order to read or download Defy Dishmaid 8 Manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Defy Dishmaid 8 Manual . To get started finding Defy Dishmaid 8 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Defy Dishmaid 8 Manual



Safety information At time of delivery. Check packaging and dishwasher immediately for signs of transport damage. If the appliance is Please dispose of packaging materials properly. During installation. Site the dishwasher and connect it up in accordance with the installation instructions. The dishwasher must not be connected to the electricity supply while installation is being carried out. Ensure that the domestic wiring is properly earthed. The mains electricity supply must conform to the details shown on the dishwasher nameplate. Do not connect the dishwasher to the electricity supply via an extension cable. After the appliance has been installed, the mains plug should still be easily accessible. During installation, the power supply cord must not be excessively or dangerously bent or flattened. During normal use. The dishwasher must only be used by adults for the washing of household dishes and cooking utensils. This appliance cannot be installed outdoor, not even if the area in which it is installed is covered by a Do not place any heavy objects or stand on the door when it is open. The appliance could tip forward. The water inside the dishwasher is not suitable for drinking. Do not use solvents of any kind inside your dishwasher. They could cause an explosion danger. Open the door very carefully if the dishwasher is operating. There is a risk of water squirting out. Do not touch the heating element during or after a wash cycle. Fundamental rules to follow when using the appliance If your family includes children. Keep detergents out of the reach of children, who must also be kept away from the dishwasher when The appliance is not for use by young children of infirm persons without supervision. <http://www.pszczelimiod.pl/uppics/crosman-model-1377-manual.xml>

- **defy dishmaid 8 manual, defy dishmaid 8 manual pdf, defy dishmaid 8 manual download, defy dishmaid 8 manual free, defy dishmaid 8 manual 2017.**



DEFY DISHWASHER
Premium

DEFY DISHWASHER
Super Silent

DEFY DISHWASHER

These different dishwasher
are described in this manual.
Please identify your model from the
description on the control panel and read
only the relevant instructions.

www.defy.co.uk

Page	Index
1	Dear customer
1	Delivery site
1	Check of installation
1	Water connection
1	Drain requirements
1	General precautions
1	Use control panel
1	Interior features
1	The built-in specifications
1	Water softeners
1	Electrical
1	Water inlet
1	Loading
1	Unloading
1	Travelling
1	Polished Pottery Operations
1	Programme chart
1	Polished Silverware Operations
1	Programme chart
1	Polished Operations
1	Programme chart
1	Mixing
1	Timable cleaning
1	Service Channels
1	Warranty

YoungIf the appliance malfunctions, turn off water supply to the appliance and disconnect the plug fromTo maintain the EFFICIENCY and SAFETY of this appliance,we recommendIf the supply cord is damaged, it must be replaced by the manufacturer or its service agentWhen disposing of old appliances. Appliances which are no longer being used must be made inoperable by cutting the power supplyTake the appliance to a designated waste disposal center. Dangerous voltage. Children could get locked in the appliance risk of suffocationTherefore Remove the mainsDamage the door lock soPositioning the appliance. Positioning the appliance in the desired location. The back should rest against the wall behind it, and theThe dishwasher is equipped with water supply and drainLevelling the appliance. Once the appliance is positioned, adjust the feet screwing them in or out to adjust the dishwasher,Cold water connectionIf the water pipes are new or have not been used for an extended period of time, let the water run to make sure that theIf this precaution is not taken,The appliance is to be connected to the water mains using new hosesets and that oldWater pressure 0.031.0MPa. A Pressure limiting valve isDrain hose connection. Insert the drain hose into a drain pipe with a minimum diameter of 4cm, or let it run into the sink, makingIf necessary, fit a syphon trap Ubend with a connecting piece forThe connecting piece for syphon trap Ubend must be solidly fastened to the wall toElectrical Connection. After making sure that the voltage and frequency values for the current in the home correspond to thoseIf the electrical socket to which the appliance must be connected is not appropriate for the plug, replaceThe dishwasher plug must be accessible even when the appliance is installed as a builtin unit so that maintenance can be done safely.Closeup view control panelF Heat Indicator Light. G Knob For Selecting Cycle. Dishwasher interiorHow to fill the rinse aid and the detergent dispenser.<http://ntg-holdings.com/pic/crosman-model-17-manual.xml>

DEFY DISHMAID PREMIUM MANUAL

YWSMJTYQZ | PDF | 182.35 | 26 Nov. 2013

TABLE OF CONTENT

[Introduction](#)

[Brief Description](#)

[Main Topic](#)

[Technical Note](#)

[Appendix](#)

[Glossary](#)

Rinse aid. This product makes dishes sparkle and helps them to dry without spotting. The dispenser is located on the right side of the dishwasher. When the low rinse aid indicator lights, you must load rinse aid. Loading the rinse aid. Regardless of the type of detergent dispenser installed on your appliance, there are 6 different settings; the normal dosage setting is 2. If drops of water remain on the dishes or if the dishes have detergent. Detergent specifically intended for use with dishwashers must be used. The dispenser must be refilled before the start of each wash cycle. The detergent for the prewash cycle should be poured into the dispenser. After the detergent has been placed in the dispenser, close the dishwasher door. Dishwasher detergents are strongly alkaline. They can be extremely dangerous if swallowed. Check that the detergent receptacle is empty after completion of the wash cycle. What you should not put into the dishwasher. Cutlery and tableware manufactured in whole or part from wood. They become faded and unsightly. In the decorative patterns on such items will not be dishwasherproof. Plastic objects that are not resistant to hot water, copper and pewter utensils are also not suitable. Decorative patterns printed or painted onto the surface of crockery, glasses, etc., aluminium and silver. Some types of glass can become opaque in appearance after they have been washed many times in a dishwasher. Highly absorbent materials, such as sponges and towels, should never be placed in the dishwasher. Our recommendation. In future, only purchase table or kitchenware that has been confirmed as being dishwasherproof. Dishes or cutlery that have been soiled by tobacco ash, wax, lubricating grease or paint, damage to glassware and other dishes. Possible causes. Suggested remedy. If necessary, seek further information from the manufacturer. Select a programme with a low temperature and a short duration as possible.

To prevent damage, take glass and cutlery out of the dishwasher as soon as possible after the wash cycle. Before placing the dishes in the dishwasher, remove larger food items. If the pots and pans have baked on food that is extremely hard, this will eliminate the need for extra wash cycles. Pull out the rack to load the dishwasher. Load for 12 Standard Settings. How to use the lower rack. We recommend that you place the most difficult to clean items. It is preferable to place serving dishes and lids on the sides of the lower rack. Pots, serving bowls, etc. Deep pots should be slanted to allow the water to flow out. The silverware basket can be doubled see fig. D so that silverware should be placed in the silverware basket with knives and other utensils with sharp points must be loaded in the basket with their points facing outwards. The upper rack is designed to hold more delicate and lighter items. Position the dishes and cookware

so that they do not getThe upper rack can be adjusted for height by using the knobsAdjust the upper basket to the higher level and you haveShelf. Lean tall glasses and those with long stems against the shelfnot against other items to be washed. Place glasses, cups and small bowls on the additional cup rack. The additional cup rack can be swivelled in or out as requiredWashTypes of load. Description of cycle. Very dirty dishes,Prewash with hot water. Rinses with cold water. Rinse with hot water. Drying.Prewash use cold water. Rinse with cold water. Drying.Rinse with cold water. Hot rinse. Drying. Very lightly soliedLoad. Detergent. Rinse. Extended Aid. Prewash. WashCold rinse.Drying.Short cold wash to prevent food residue fromProgramme selection. The most appropriate programme can be identified by comparing the type of crockery, cutlery, etc., asEarn savings. If only a small number of dishes have been loaded into the dishwasher,selecting a programme thatProgramme data. The stated programme data are based on standard operating conditions.



INSTALLATION & OPERATION MANUAL



FLIGHT TYPE DISHWASHERS

MODELS
STPC
STPCW
STPCW-D
STBUW

For additional information on Stero or to locate an authorized parts and service provider in your area, visit our website at www.stero.com.

STERO, A DIVISION OF ILLINOIS TOOL WORKS INC.
WWW.STERO.COM

3200 LAKEVILLE HWY.
PETALUMA, CA 94954
Telephone: 800-762-7600
Fax: 707-762-5036

<http://ninethreefox.com/?q=node/17517>

The values can vary considerably according toTurning on the Appliance. Starting a wash cycle. Make sure that the plug for the appliance is inserted into the wall socket. Make sure that the water supply is turned on to full pressure. Load the dishes. Pour in the detergent. Press the Power button, and the "POWER" light will turn on. Turn the knob located on the right of the control panel until the number or symbol for the cycle settingAfter five seconds the "POWER" light will flash, the wash cycle will begin. Note When washing, the knob will not rotate itself.When the buzzer constantly beeps six times, the "POWER" light will turn on and the cycle has finished. TurnWait a few minutes before unloading the dishwasher to avoid handling the dishes and utensils whileThey will also dry better. Cancelling or modifying a wash cycle setting. A cycle that is underway can only be modified if it has been running for a short time. Otherwise, theRotate the knob to the mark of "Reset" then selectThis will allow you to save on water and energySelect the programme see the paragraph entitled "Turning on the Appliance" After Every Wash. After every wash, turn off the water supply not necessary for models with "Aquastop" to the applianceRemove the plug. Before cleaning or performing maintenance, always remove the plug from the socket. Do not run risks. No solvents or

Abrasive Cleaning Products. To clean the exterior and rubber parts of the dishwasher, do not use solvents or abrasive cleaning. To remove spots or stains from the surface of the interior, use a cloth dampened with water and a little. Moving the Appliance. If the appliance must be moved, try to keep it in a vertical position. If absolutely necessary, it can be. Seals. One of the factors that cause odors to form in the dishwasher is food that remains trapped in the seals. Periodic cleaning with a damp sponge will prevent this from occurring. The door should not be left in the open position since this could present a tripping hazard.



When You Go on Holiday. When you go on holiday, it is recommended that you run a wash cycle with the dishwasher empty and. Regular inspection and maintenance of your appliance helps to prevent problems from occurring. This. Overall condition of appliance. Check that no grease or scale has accumulated on the inside of the dishwasher. If you discover any deposits. Rinseaid. Check the LOW RINSE AID indicator " 7 ", on the control panel. Top up with rinseaid, if required. The filters " 8 ", " 9 " prevent larger particles of food in the water. After undoing the coarse microfilter " 8 ", the filter unit " 9 " Insert the filter unit " 9 " and tighten the coarse microfilter. Lime and remnants of food in the washing water can block the. Inspect the nozzles in the spray arms for blocked holes. If necessary, pull the lower arm " 11 " upwards and lift it off. Unscrew the upper spray arm " 10 ". Clean both spray arms under running water. Refit the spray arms. Ensure that the lower arm has locked. Resolving minor problems yourself. Experience has shown that you can resolve most problems that rise during normal daily usage yourself. The following list of common occurrences and Problems. Appliance does not start up. Fault with fuse in mains electricity supply. Plug not inserted in wall socket. Appliance door not closed properly. Programme has not been chosen. Water tap not turned on. Blocked strainer in water intake hose. Do not forget that repairs should only be carried out by a qualified specialist. Improper. When the alarm sounds in a series of 2 beeps, pause, 2 beeps, pause. When the alarm sounds in a series of 3 beeps, pause, 3 beeps, pause. When the alarm

sounds in a series of 6 beeps, pause, 6 beeps, pause. Spray arm rotates with difficulty. Spray arm is blocked by small items or food remains. Lid in detergent compartment cannot be closed. Detergent compartment has been overfilled. Mechanism is clogged with remnants of detergent. Indicator lamps do not extinguish after washing has finished.



Power Button is still set to ON. Remnants of detergent stuck inside dispenser. Compartment was damp when it was filled up with detergent. Compartment must be dry before Water remains inside appliance after programme has ended. Blockage or kind in drainage hose. Pump is jammed. Filters are blocked. The programme is still running. Wait for the programme to end. Unusual amount of foam is increased. Normal washing up liquid has been poured into the rinseaid container. Remove any spilled rinse aid with a cloth as it could otherwise lead to excessive foaming during the Appliance stops suddenly while washing is taking place. Cut off electricity supply to appliance. Water supply has been interrupted. Knocking sound can be heard while washing is taking place. A spray arm is knocking against the dishes inside the appliance. Rattling sound can be heard while washing is taking place. Crockery has not been stacked properly inside the appliance. This is caused by the way the water pipes have been laid and it has no effect upon the way the Remnants of food are stuck to the dishes, cutlery, etc. Dishwasher was not loaded properly. Jets of water could not reach all parts of the dishes, etc. Too many items in the rack. Items in the rack were touching each other. Not enough detergent was added to dispenser. Selected wash programme was not intensive enough. Rotation of spray arm was obstructed by dishes, etc. Nozzles in spray arm are blocked by remnants of food. Filters have been incorrectly fitted. Wastewater pump is jammed. White stains are left on crockery, glasses have a milky appearance. Not enough detergent was added to dispenser compartment. Amount of rinseaid was set too low. Dishes, cutlery, etc. have not been dried. Selected programme did not include drying function. Items were removed from dishwasher too soon. Glasses have a dull appearance. Tea stains or traces of lipstick have not been completely removed. Detergent does not have a sufficient bleaching effect.

Washing temperature was set too low. Traces of rust on cutlery. Cutlery is not sufficiently rustproof.

Glasses become clouded and discoloured; coating cannot be wiped off. Unsuitable detergent was used. Glasses are not dishwasherproof. Smears left behind on glasses and cutlery; glasses have acquired a metallic appearance. Amount of rinseaid set too high. WidthDepthHeightCapacity. Mains water pressure. Power supply. Maximum current intensity. Total absorbed powerNotes on waste disposal. Old appliances still have some residual value. An environmentfriendly method of disposal will ensureWhen an appliance has reached the end of its working life,unplug it from the mains.Cut through theDestroy the door locking mechanism. This will ensure that children at play cannot become locked insideYour new appliance was protected by suitable packaging while it was on its way to you. All materialsPlease make a contribution toDo not allow children to play with any parts of the packaging. There is a risk of suffocation by theUpto date information concerning options for disposal can obtained from your retailer or local municipal administration. General information. Measures must be taken to ensure that builtunder and builtin units that are subsequently resitedThis can be achieved by bolting the dishwasher toInformation on comparability tests implemented in compliance with. Appliance loaded in accordance with standard specifications. Example of loaded dishwasher See fig. 1 and 2. Capacity 12 place settings. Comparability programme NORMAL wash. Rinseaid setting 5Wiring box. Water level switchOverflowDrain pumpThermal cutout. Heating element. Temperature sensorThermal cutout. Heating relay. Water connection. Drain requirements. General precautions The control panel. Interior features. Technical specifications. Water softener. Detergent. Rinse aid. Loading. Cleaning. Dishmaid 3 Operation. Programme chart. Moving. Trouble shooting. Service Centres. Warranty.

<http://www.nandomoraes.com.br/wp-content/plugins/formcraft/file-upload/server/content/files/1628ff487e5691---Case-580ck-manual-download.pdf>

2 2 2 2 2 3 4 5 5 6 7 8 8 11 12 13 14 15 16 17 You can rely on Defy. To simplify DDW 156 DDW 157 1 2 3. 18 Summary of content 18 pages Page 1 OWNERS MANUAL You can rely on Defy. To simplify Page 2 2 2 2 2 3 4 5 5 6 7 8 8 11 DEFY DISHMAID 3 DDW 156 DDW 157 Index Dear customer. Before use. Electrical connection. Water connection. Drain requirements. General precautions The control panel. Interior features. Technical specifications. Water softener. Detergent. Rinse aid. Loading. Cleaning. Dishmaid 3 12 13 Operation. Programme chart. 14 15 Moving. 16 17 Service Centres. Trouble shooting. Warranty. www.defy.co. Page 2 Dear Customer You are now the proud owner of one of the finest and most modern products that todays technology can produce. Please read all the instructions carefully as they contain information on how to operate and care for your dishwasher so that you may gain the maximum benefit from it. Store this book in a safe place for future reference. Before use Unpacking Remove all packaging material, accessories and documentation from the machine. Damage Do not use the machine if it has been damaged in transit. Page 3 General precautions Children Never allow children to play with the dishwasher. Detergents contain irritants and abrasives which could affect the eyes, mouth and throat. Keep detergents out of reach and only put them into the machine just before starting a washing programme. Dishwasher waste water is not suitable for drinking. Never allow children to play on or sit on the door when it is open. Please ensure that packaging material is disposed of in a responsible manner. Page 6 Salt container Special salts are used as a water softening agent in dishwashers Salt container The dishwasher is equipped with an automatic salt release system. The salt container needs to be filled with regenerating salts specially developed for dishwashers. Small grained or powdered salt is recommended.

Do not use table salt or edible salt as these contain insoluble substances. S AL Z TU Z T SEL The dishwasher requires lime free water for optimum operation. Page 7 Detergent Only use detergents specifically intended for dishwashers Adding detergent The detergent and rinse aid dispensers are on the inside of the door. If the dishwasher is considerably full and the dishes are relatively dirty, fill the main container A up to the 25cm level. If the dishwasher is not quite full and the dishes are only

slightly soiled, fill the main container A to the 15cm level. Page 8 Rinse aid Only use rinse aid specifically intended for dishwashers Rinse aid prevents water and calcium streaking on dishes and speeds up the drying process. It is advisable therefore to always ensure that there is an adequate amount of rinse aid in the dispenser. You can adjust the amount of rinse aid released during a programme by turning the dispenser regulator C The regulator level may be set between 1 minimum and 6 maximum. Page 9 Loading The dishwasher has a twelve place setting capacity There are three separate baskets in the dishwasher. 1 The upper basket is used for cups, saucers, glasses and smaller dishes. The upper basket has glass holders which may be lifted and then folded to accommodate larger items. 2 Glass Support depending on the model When placing the glasses or goblets with a long grip, lean them against the glass support, the edge of the basket or the shelf but not against the other pieces. Page 10 Loading The upper basket has a height adjustment facility. The basket may be lowered to facilitate the loading of larger items. The adjustment method varies from model to model and you should check which method is pertinent to your machine. Defy Dishmaid Release the latches on both the right and left tracks by opening them sideways. Roll the basket forwards to remove it. Position the basket so that the upper set of rollers engages in the tracks and close the latches.

Page 11 Cleaning Always disconnect the appliance from the electrical supply before cleaning it Cleaning the cabinet Wipe up any detergent, softener and other spills as they occur with a soft damp cloth. Periodically clean the cabinet, the inside of the door and door gasket with a damp warm soapy cloth, rinse and dry. Do not use abrasive or corrosive substances. Cleaning the filters To ensure optimum performance, the filters should be cleaned regularly. Page 12 Operation Defy Dishmaid Progress indicator lights Progress of the wash cycle may be monitored by observing the progress indicator lights on the control panel. 12 Operation Open the door of the machine. Load the dirty dishes into the baskets. Check that the upper and lower spray arms can rotate freely. Add detergent. Check the rinse aid and water softener salt indicators and replenish if necessary. Close the dishwasher door. Switch on the electricity. Remove the drain hose. Ensure that the hoses are not twisted or kinked during transport. Only transport the machine in an upright position. Page 15 Service Centres If you have followed the instructions and still have a problem, contact the nearest Defy Service Centre. They will be able to advise you on any aspect of the product or send a qualified technician to repair it. BLOEMFONTEIN CAPE TOWN DURBAN EAST LONDON JOHANNESBURG Commercial Head Office, Administration, Distribution, National Groups, Tel. Sales, Contracts and Credit. POLOKWANE PORT ELIZABETH PRETORIA. 160 Long Street, Hilton, Bloemfontein 9301. Tel. 051 400 3900 Bloemfontein. Page 16 Warranty This certificate is issued by DEFY APPLIANCES LIMITED manufacturers of Defy and Ocean products, hereinafter the Company, to the original purchaser only, of the appliance described on the certificate and shall constitute the only warranty given in respect of this appliance. Water softener. Detergent. Rinse aid. Loading. Cleaning. Dishmaid 3 Operation. Programme chart. Moving. Trouble shooting. Service Centres.

Warranty. 2 2 2 2 3 4 5 5 6 7 8 8 11 12 13 14 15 16 17 You can rely on Defy. To simplify DDW 156 DDW 157 Next To simplifyPage 3 General precautions. Children The door of the machine has been designedPage 4 The control panelPage 7 DetergentAdding detergent E. The detergent and rinse aid dispensers are on. Page 8 Rinse aidThere are three separate baskets in the dishwasher.Page 11 CleaningCleaning the cabinetPage 12 OperationPage 13 Programme chartPage 16 Warranty. Hi Jacky Marcus, Just keep the start button pressed in for about 5 10 seconds. Should reset the cycles. Hope this helps Where can I buy another thermostat for my defy dishmaid Try RepairClinic.Com or PartsDirect.Com. What is the problem with the machine When turning the selection knob nothing happens. I turned it again slowly and it sounded l When turning the selection knob nothing happens. I turned it again slowly and it sounded l. Go by what they really know or if they steal Hope it is what your looking for. Product manuals It sounds like the control. I interrupted it and now it wont reset I interrupted it and now it wont reset Try powering it down unplug for five minutes and try again.

DD603SS Built-in Dishwasher Answer questions, earn points and help others. To simplify Unpacking. Know your product. Safety compliance with local Installation. Electrical connection. Gas connection. Temporary installation. Check for leaks. If you smell gas. Using the hob. Flame failure safety cutout. Action in the event of a burnback. Flame adjustment. Cleaning removable parts. Cleaning the hob. Cleaning the gas jets. Care guide for stainless steel. Safety notes. Technical specifications. Owner's responsibility. Trouble shooting. Defy Service Centres. Warranty. Installer's details. Purchase details Safe Appliance. LP Gas Safety Association Introduction. Congratulations on the purchase of this quality appliance. We trust that you will enjoy many years of trouble free use.

Important Read these Keep these instructions for future reference. This book Unpacking. Remove all packaging material and ensure that it is disposed of in a responsible manner. Plastic bags should be cut up to prevent children playing with them and accidentally If the appliance is damaged in any way, do not use it. Report the damage to your dealer, who To avoid accidental injury, care should be taken when handling the hob prior to Know your product Permanent installation. Important information for the user. The appliance may only be installed by a registered LP Gas installer. All registered Ask to be shown QCC number below. Upon completion of the installation, the installer is required to explain You will be asked Note Your invoice is required in the event of you wishing to make a warranty claim. Important information for the installer. This appliance may only be installed by a LP Gas installer registered with the LPGSASA. The appliance must be installed in If in doubt check with the relevant authority before Upon completion of the installation you are required to fully Note. This appliance is supplied ex factory with jets and air settings for use with LP gas The necessary installation instructions, including gas and electrical connections are The manufacturer declines liability for injury to persons or damage caused due to non Preparing the cabinet. The hob should be installed in a ventilated cupboard fitted with a sturdy worktop. Prepare the aperture hole in the countertop as per the measurements given below. Ensure a safe distance is left between the hob, kitchen walls and furniture, bearing in Fitting the hob Note. If the hob is not installed above an oven, a separator baffle must be installed. This appliance must be earthed and the manufacturer and the seller The mains supply must correspond with the data specified on the Nor should it come into contact with If the mains lead is damaged it should be replaced by a qualified Gas connection.

This appliance uses LPG Liquid petroleum or bottle gas The manufacturer and the seller do not accept responsibility for any damage due to Flexible hose Not supplied. Any hose that is used to connect the stove to the gas system Ensure that pipe clamps are tightened correctly and are of good quality. Gas cylinder Not supplied. For best results we recommend that gas cylinders with a Regulator Not supplied. A 2,8 kPa LPG gas regulator which complies with SANS 1237 Temporary installation. A flexible hose connection from the gas appliance to the cylinder can be made. Ensure that pipe clamps are tightened correctly and are of good quality. See sketch on next page. Gasket. Flexible hose Hob gas pipe Al Copper pipe.

<http://www.raumboerse-luzern.ch/mieten/ecs-k7som-manual>